



Solutions For Industry

This version issued: September 2017

Product Name: **ANTI FREEZE ANTI BOIL - RTU**

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name TREBLEX INDUSTRIAL PTY LTD
Address U1 / 26 Ilda Road, CANNING VALE, WA, AUSTRALIA, 6155
Telephone /Fax (08) 9456 5825 (08) 9456 5875
Emergency 0409 084 044

Web Site <http://www.treblex.com.au>

Synonym(s) ANTIFREEZE • TAF50/20 - PRODUCT CODE

Use(s) ANTIFREEZE • COOLANT • ENGINE COOLANT.RTU
SDS Date 27 July 2015

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R22 Harmful if swallowed.

SAFETY PHRASES

S2 Keep out of reach of children.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated **DG Class** None Allocated **Subsidiary Risk(s)** None Allocated
Packing Group None Allocated **Hazchem Code** None Allocated **EPG** None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
ETHYLENE GLYCOL	C2-H6-O2	107-21-1	>46%
WATER CONDITIONING AGENT(S)	Not Available	Not Available	<4%
WATER			50%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).

Advice to Doctor Treat symptomatically

Product Name : **ANTI FREEZE ANTI BOIL**

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air.
Fire and Explosion	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Water, foam, carbon dioxide, or dry chemical. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES


Spillage	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Prevent spill entering drains or waterways.
-----------------	--

7. STORAGE AND HANDLING

Storage	Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, phosphorus pentasulphide, sodium hydroxide, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Store as a Class C1 Combustible Liquid (AS1940).
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
Biological Limits	Ethylene glycol (vapour) No biological limit allocated.	ASCC (AUS)	20	52	40	104
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.					
PPE	Wear splash-proof goggles, neoprene or butyl or rubber gloves and coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator.					



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	CLEAR GREEN LIQUID	Solubility (Water)	SOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	1.1 (Approximately)
pH	10.5 (33% solution)	% Volatiles	< 5 %
Vapour Pressure	0.01 kPa (Approximately)	Flammability	CLASS C1 COMBUSTIBLE
Vapour Density	NOT AVAILABLE	Flash Point	116°C
Boiling Point	190°C	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		

Product Name : **ANTI FREEZE ANTI BOIL**

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides) and phosphorus pentasulphide.
Decomposition	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. At room temperature ethylene glycol has a low vapour pressure and therefore an inhalation hazard is not anticipated unless heated or sprayed. Chronic exposure may result in kidney and central nervous system (CNS) damage.
Eye	Contact may result in irritation, lacrimation, pain and redness.
Inhalation	Over exposure may result in mild respiratory irritation. High level exposure may result in headache, nausea, dizziness and central nervous system (CNS) depression. Due to the low vapour pressure, an inhalation hazard is not anticipated with normal use.
Skin	Contact may result in drying and defatting of the skin, rash and dermatitis.
Ingestion	Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, drowsiness and unconsciousness. Chronic exposure may result in kidney damage. Aspiration may result in chemical pneumonitis and pulmonary oedema.
Toxicity Data	ETHYLENE GLYCOL (107-21-1) LC50 (Inhalation): 10 876 mg/kg (rat) LD50 (Ingestion): 1650 mg/kg (cat) LD50 (Skin): 9530 ug/kg (rabbit) LDLo (Ingestion): 398 mg/kg (human) TCLo (Inhalation): 10,000 mg/m3 (human - cough) TDLo (Ingestion): 5500 mg/kg (child - anaesthesia)

12. ECOLOGICAL INFORMATION

Environment	Ethylene glycol will mainly exist in the vapour phase in the ambient atmosphere where it will be degraded by reaction with hydroxyl radicals. Expected to be very highly mobile in soil. Not anticipated to volatilise from moist soil or water surfaces. Biodegradation in both soil and water is expected to be a major fate process for this compound. Not expected to bioconcentrate in aquatic organisms.
Ecotoxicity	Not classified as dangerous to the aquatic environment.
Persistence / Degradability	Expected to be inherently biodegradable.
Mobility	Expected to remain in water or migrate through soil.

13. DISPOSAL CONSIDERATIONS

Waste Disposal	For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated				
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

15. REGULATORY INFORMATION

Poison Schedule	Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

ETHYLENE GLYCOL: Has been reported to cause teratogenic and mutagenic effects, however the doses recorded for these effects are extremely high. For example experimental rat studies by the oral route have shown that ingestion of 8.5 g/kg by pregnant rats in their 6-15 day of gestation caused teratogenic effects. This equates to the ingestion of 500 ml of ethylene glycol by a 60 kg women for similar effects to occur. Exposure at such levels is not reported in industry.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

It is based on information concerning the product which has been provided by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

